

VCLX 2 Charger

SKU: 8475-0146

VCLX 2 Battery Charger



PRODUCT DESCRIPTION

The Anton/Bauer VCLX 2 Charger features magnetic connectivity with 5 hour charging time to save you time and storage space.

A standard IEC Cable, included, is required for connecting the charger to a mains outlet. A 3 pin XLR cable, not included, is required to connect the charger to the battery. Wide range mains input compatibility (90~240 VAC, 50-60 Hz) automatically adapts to any mains source worldwide.

Using an advanced charge algorithm this has resulted in the fastest charge possible in the block battery market.

Key Features

- Input 90~ 240 VAC, 50-60 Hz
- 5 hour charging time
- Magnetic Connectivity to VCLX NM2
- Operating temprature between -20°C to +60°C (-4°F to 140°F)

TECHNICAL SPECIFICATIONS

Charging Specification	Simultaneous
Built-In Discharge	No
Charging Positions	1
WiFi Enabled	No
Family	VCLX 2
Height	63 mm 2.48 in
Width	12.4 cm 4.88 in
Depth	24 cm 9.45 in
Weight	1.36 kg 3 lb
XLR Connector	No
AC Power Supply	Yes
LCD Display	No
LED Indicators	No
Touch Screen	No
Charging Capability	Single Unit Charger
Power Supply	No