

DIONIC XT

Battery Series

The Power Behind the Scene

Peak performance in compact form. For demanding cinematographers, DIONIC XT is the gold standard for high-performance, consistently reliable mobile power in temperatures from -20C to 60C (-4F to 140F). Delivering 12 amps of constant current to power cameras and accessories simultaneously, and with sophisticated charging technology extending its lifecycle to provide the same consistent level of power throughout its life, DIONIC XT is the perfect choice where dependable power is mission critical.



- 156Wh or 99Wh lithium-ion battery
- Gold-Mount or V-Mount options
- 12A continuous draw (20A peak, 75A inrush)
- P-Tap and Smart USB ports
- Backlit multifunction LCD display
- >1000 cycle life (flat capacity curve)



Premium Power.

Drive high-performing cine gear

Delivering 12A of consistently reliable premium power (with 20A peak and 75A inrush) you can count on DIONIC XT to provide dependable power for sensitive high-end imaging equipment. Engineered to withstand the rigors of set life, advanced battery management technology prolongs the life of the battery while protecting your camera, monitor and powered accessories. Run cine and documentary cameras for over two hours with the lightweight, ultra-tough DIONIC XT 90 or power LED panels such as the Litepanels Gemini series at full intensity with the compact DIONIC XT 150.



Accurate Intelligence.

Confirm runtime and advanced diagnostics.

Use the onboard backlit LCD or your camera viewfinder to see exactly how much runtime remains in minutes or as a percentage, simply tap the Battery to scroll through performing other real-time diagnostics to keep your battery and equipment performing perfectly. DIONIC XT smart technology calculates everything being powered - even devices powered by the USB and P-TAP ports - leaving you free to focus on the action in front of your camera.



Endurance tested for action.

Power and Performance when it counts.

Designed to perform on the toughest sets, DIONIC XT batteries are the compact, reliable, travel-safe choice when you need to capture the shot first time - every time! High quality cells in a rugged case ensure consistent power to the most demanding users in temperatures from -20C to 60C (-4F to 140F). when it's time for Action, with DIONIC XT you have the power.



Air transport safe.

Reliable power you can take anywhere.

Cleared for take-off. DIONIC XT batteries are safety certified to comply with UN38.3 IATA lithium-ion battery regulations. Independent safety lab testing confirms that DIONIC XT meets the stringent UN regulations and is built to the highest standard.



DIONIC XT G90 DIONIC XT V90 DIONIC XT G150 DIONIC XT V150

SKU	8675-0125	8675-0126	8675-0127	8675-0128
Capacity	99Wh	99Wh	156Wh	156Wh
Height	5.1" / 13cm	5.1" / 13cm	5.1" / 13cm	5.1" / 13cm
Depth	2.1" / 5.5cm	2.1" / 5.5cm	2.7" / 7cm	2.7" / 7cm
Width	3.8" / 9.7cm	3.8" / 9.7cm	3.8" / 9.7cm	3.8" / 9.7cm
Weight	1.76lbs / 0.8kg	1.76lbs / 0.8kg	2.4lbs / 1.1kg	2.4lbs / 1.1kg
Operating temperature range - Discharge	-4°F to 140°F (-20°C to +60°C)			
Maximum Discharge Rate	12A			
Output Voltage	Nominal 14.4V Operating 10.0V - 16.8V			