

# DIONIC XT BATTERY SERIES

## V-MOUNT & GOLD MOUNT

### Raising the bar on Performance and Reliability

The Dionic XT battery series is a powerful and durable Li-ion solution in a compact, robust design to complement cine-style cameras like the ALEXA MINI, RED WEAPON and Blackmagic URSA Mini.



#### INTELLIGENT INNOVATION

Using Anton/Bauer's award winning mobile power excellence, the Dionic XT technology provides uniform performance throughout its long life. The intelligent on board battery management system enables you to manage your fleet efficiently



#### LIFETIME VALUE

The Dionic XT delivers powerful performance in a range of environments. Engineered to be recharged more times extending its cycle life compared to the other battery systems. Offering the best ROI and lowest management overhead



#### VERSATILE SOLUTIONS

V-Mount and Gold Mount Dionic XTs are certified as transportable by air for those long distance jobs. They are also cross compatible with multiple brand chargers and superior in powering accessories such as portable LED lighting



#### RELIABLE, COMPACT AND POWERFUL

You can count on Dionic XT to power the most mission critical equipment with consistently high performance. Save valuable travel space with these reliable smaller form batteries. Dionic XT raises the bar on performance and reliability.



**Dionix XT90G****Dionix XT90V****Dionix XT150G****Dionix XT150V****Capacity**

99Wh Nominal

99 Wh Nominal

156 Wh Nominal

156 Wh Nominal

**Height**5.1 inches  
(13 cm)5.1 inches  
(13 cm)5.1 inches  
(13 cm)5.1 inches  
(13 cm)**Depth**2.1 inches  
(5.5 cm)2 inches  
(5.1 cm)2.7 inches  
(7 cm)2.6 inches  
(6.6 cm)**Width**3.8 inches  
(9.7 cm)3.8 inches  
(9.7 cm)3.8 inches  
(9.7 cm)3.8 inches  
(9.7 cm)**Weight**1.76 lbs  
(0.8 kg)1.76 lbs  
(0.8 kg)2.4 lbs  
(1.1 kg)2.4 lbs  
(1.1 kg)**Environmental Data - All Variants****Operating temperature range****Charge** 0°C to +45°C (-32°F to +113°F)**Discharge** -20°C to +60°C (-4°F to 140°F)**Electrical Data - All Variants****Maximum Discharge Rate** 173W or 12A**Output Voltage** Nominal 14.4V Operating 10.0-16.8V